



CAPTAIN

Built for City Delivery

CAPTAIN-E

GVW 5280kg **4-Wheeler**

CAPTAIN-C

GVW 7500kg **6-Wheeler**



All Pictures shown are for illustration purpose only.



TECHNICAL SPECIFICATION

Model		CAPTAIN E	CAPTAIN C	
Chassis Details	Model Code	EM98-101J	CA9R-301J	
	G.V.W (Gross Vehicle Weight)	5280kg	7500kg	
	Cab Width	1880mm	2030mm	
	Maximum Speed	100km/h	100km/h	
	Gradeability	35%	36%	
	Curb Weight	1730kg	2790kg	
	Turning Radius	7.5m	8.0m	
Engine	Model	JE493ZLQ4	Cummins ISF3.8s4R154	
	Type	Diesel, in-line 4-cylinder, Turbo Intercooler		
	Fuel Injection System	ECU Control Common Rail Injection		
	Displacement (cc)	2771	3760	
	Max. Output (kW/PS@rpm)	80 / 108 @ 3400	115 / 156 @ 2600	
	Max. Torque (N.m@rpm)	260 @ 2,000	500 @ 1900	
	Emission Standards	Euro IV		
Clutch	Emission Control	EGR + DOC + POC		
	Form	Diaphragm Spring		
Gearbox	Diameter	Φ265mm	Φ350mm	
	Type	5 Speed MT	6 Speed MT	
	Model	WLY-5GT32	FAST-C6J55T	
	Gear Ratio	1 st	4.714	6.18
		2 nd	2.467	3.33
		3 rd	1.650	2.08
		4 th	1.000	1.39
		5 th	0.719	1.00
		6 th	-	0.78
	Reverse	4.505	5.57	
Final	4.875	4.33		
Frame	Cross-sectional Dimensions(mm)	190 x 55 x 4.5	192 x 65 x 6	
	Width (mm)	760	800	
	Layer	Single Layer		
Braking	Service Braking system	Dual-circuit hydraulic brakes with vacuum assist.	Dual-circuit Air brakes	
	Front / Rear	Drum / Drum		
	Auxiliary Brake system	Exhaust Brake		
	Parking Brake	Mechanical internal-expanding, acting on transmission output shaft	Mechanical internal-expanding, acting on rear wheels	
Axle	Front	Type	Reversed Elliot, I-Beam	
		Capacity	2,200kg	
	Rear	Maker	BANGLE	DANA
		Type	Full Floating, Pressed welding housing, Hypoid Gear	
		Capacity	3,500kg	5,500kg
		Maker	BANGLE	DANA
Suspension	Front	Type	Multi Leaf Spring with Dual Acting Shock Absorber	
		Number of Springs	6	
	Rear	Type	Multi Leaf Spring, Dual Acting Shock Absorber and Stabilizer Bar	Multi Leaf Spring with Dual Acting Shock Absorber
		Number of Springs	6 + 5	10 + 7
Tyre	Wheel Type	6 Stud Tubeless Tires		
	Wheel Size	7.00R16-14PR	215/75R17.5	
	Rim Size	5.50F-16 Steel	6.00 x 17.5 Steel	
	Number of Tires	4 + 1	6 + 1	
Cab	Tilting	Mechanical Type		
	Steering	Recirculating ball with Hydraulic power assistance		
Safety Features	ABS + ESC	Yes		
Electrical	Reverse Sensor	Yes		
	Battery	12V, 100AH	12V, 100AH x 2pcs	
Fuel Tank Capacity	Alternator	14V - 80A	28V - 70A	
		76L (Steel)	120L (Aluminium)	
Chassis Dimension (mm)	Overall Length (OL)	4785	6750	
	Overall Width (OW)	1930	2110	
	Overall Height (OH)	2200	2360	
	Wheelbase (WB)	2515	3800	
	Front Overhang (FOH)	1045	1145	
	Rear Overhang (ROH)	1225	1805	
	Front Tread (FT)	1613	1745	
	Rear Tread (RT)	1540	1884	

Disclaimer: The Manufacturer reserves the right to make changes to technical parameters & designs or to discontinue models without prior notice.

DONGFENG COMMERCIAL VEHICLE (MALAYSIA) SDN BHD

A Member of Sunway Group

Lot 526, Persiaran Subang Permai, Sungai Penaga Industrial Park, USJ 1, 47600 Subang Jaya, Selangor Darul Ehsan.

Tel: 03-8021 9068 Fax: 03-8021 9069

Website: <http://dongfeng.my/>

Authorised Dealership

Hock
Whatsapp: 0162007298

SUNWAY[®]
TRADING &
MANUFACTURING

© Version 11/2023