







LED Headlight



LED Tailight and Winker



LCD Digital Meter



Tools Keeper

Single Cylinder, Air Cooled, SOHC 4-Stroke 2 Valve 124.89 cm³

52.4 mm x 57.9 mm 9.3 : 1

6.66 kW / 7,000 rpm 10.5 N.m / 5,500 rpm 1.1 L (After Disassembly) 0.9 L (After Draining)

Fuel Injection (PGM-Fi) 5.6 L

Electric Auto Start 3.5 A.h 12 V

Multiplate Clutch Manual / 4 Speed - Constant Mesh

SPECIFICATIONS

Type Displacement Bore And Stroke

Compression Ratio

Max. Torque Engine Oil Capacity

Carburation Fuel Tank Capacity

Starter Battery Capacity ACG Output

Clutch Type Transmission Type



Alarm & Answer Back



Never Lower Muffler

1,712 mm x 754 mm x 1,029 mm 1,152 mm

Front : Up-side down Fork Rear : Twin

Front : 12 M/C x MT 2.75 Rear : 12 M/C x MT 3.50

Front : Hydraulic Disc Rear : Hydraulic Disc

Front : 120/80 - 12 M/C (65P) Rear : 130/80 - 12 M/C (69P)

Back Born

25°

82 mm 776 mm

160 mm

105 kg





Pearl Glittering Blue

Pearly Nebula Red

Cop Peniaga Sah:



14100 Simpang Ampat, Pulau Pinang. HQ 04 506 3333 KL 03 6259 3516 / 03 6259 3517 JOHOR 07 244 8877 / 07 244 7557 TERENGGANU 09 624 0767 / 09 624 0746 Talian Pelanggan **1800 88 3993** Waktu Operasi **Isnin - Jumaat (9pg – 5ptg). Tutup pada hari cuti umum**

hondamotorcycle.my

f



Frame Type Dimensions (L x W x H) Wheelbase Caster Angle

Trail Seat Height Ground Clearance

Suspension Type

Kerb Weight

Tyres

Brakes Type











