## **Rebel Specification**

Model	Rebel			
ENGINE & TRANSMISSION				
Туре	PC56E / Liquid-cooled, DOHC			
Displacement	471.03 cm <sup>3</sup>			
Bore X Stroke	67mm x 66.8mm			
Compression Ratio	10.7 : 1			
Clutch	Wet, Multiplate with coil springs			
Transmission	6 – speed Manual			
Final Drive	Chain			
Primary / Final Reduction	2.029 / 2.667			
Gear Reduction	Gear 1 – 3.285, Gear 2 – 2.105, Gear 3 - 1.600,			
	Gear 4 – 1.300 , Gear 5 - 1.150, Gear 6 – 1.043			
Ignition	Computer-controlled digital transistorized with electronic			
	advance			
Starter	Electric			
DIMENSION AND WEIGHT	1			
Dimensions (L x W x H)	820 x 2,190 x 1,093			
Wheelbase	1,490 mm			
Caster Angle	28° 0'			
Trail	110 mm			
Seat Height	690 mm			
Ground Clearance	136 mm			
Kerb Weight	191 kg			
Fuel Tank Capacity	11.2 L			
SUSPENSION, WHEELS & BRAKE				
Suspension Type	Front	ø41 mm Telescopic Fork, 121 mm stroke		
	Rear	Dual shocks with five-position spring-preload		
		adjustability, 93 mm stroke		
Brake Type	Front	Twin-piston caliper with single 296 x 5.0mm disc		
	Rear	Single-calliper 240 x 5.0mm disc		
Tyres	Front	130/90 – 16M/C 67H (Tubeless)		
	Rear	150/80 – 16M/C 71H (Tubeless)		

## **Honda X-ADV Specification**

Model	X - AD	V	
ENGINE			
Туре	Liquid-cooled, 4 strokes, OHC		
Displacement	745cm³		
Bore X Stroke	77mm x 80mm		
Compression Ratio	10.7 ± 0.2		
Max. Power	40.3kW @ 6,250rpm		
Max. Torque	68Nm @ 4,750rpm		
Engine Oil Capacity	4.1L		
FUEL SYSTEM			
Carburation	PGM-FI		
Fuel Tank Capacity	13.1 + 0.5/0 L		
ELECTRICAL SYSTEM			
Starter	Electric Auto Start		
Battery Capacity	11.2 AH		
ACG Output	12V		
DRIVETRAIN			
Clutch Type	Automatic Clutch Wet Multi plate Type		
Transmission Type	Mechanical (Chain Drive)		
Transmission Gear Ratio	Gear 1 - 2.666, Gear 2 - 1.904, Gear 3 - 1.454, Gear 4 - 1.200, Gear 5 - 1.033, Gear 6 - 0.837		
CHASSIS	•		
Frame Type	Diamond		
Dimensions (L x W x H)	2230 x 910 x 1345		
Wheelbase	1,580mm		
Caster Angle	27° 30'		
Trail	104mm		
Seat Height	820mm		
Ground Clearance	135mm		
Kerb Weight	238kg		
SUSPENSION, WHEELS & BRAKE			
Suspension Type	Front	Telescopic	
	Rear	Pro Link	
Rim Size	Front	17 M/C MT 3.50	
	Rear	15 M/C X MT 4.50	
Tyres	Front	120/70 R17 M/C 58H (Tubeless)	
	Rear	160/60 R15 M/C 58H (Tubeless)	
Brakes	Front	Hydraulic Double Disk	
	Rear	Hydraulic Double Disk	