Reference: Main specifications

I VELETELICE	. IVIAIII	specifications				
Grade			RZ	SZ-R	SZ	
Length (mm)			4,380			
Width (mm)			1,865			
Height (mm)			1,290	1,295		
Wheelbase (mm)			2,470			
Tread		ront (mm)	1,595 1,610		1,610	
	R	ear (mm)	1,590		1,615	
Minimum ground clearance (mm)			112	118		
Curb weight (kg)			1,520	1,450	1,410	
Seats			2			
Powertrain layout			Front-engine, rear-wheel-drive			
Engine			Inline-6 DOHC Twin-scroll turbocharger	Inline-4 DOHC Twin-scroll turbocharger		
	Engine displacement (cc)		2,997	1,998		
Max	ximum d	output	250[340]	190[258]	145[197]	
(kW	(kW[PS]/rpm) Maximum torque		/5,000	/5,000	/4,500	
Max			500[51.0]	400[40.8]	320[32.6]	
(N·	(N·m[kgf·m]/rpm)		/1,600-4,500	/1,550-4,400	/1,450-4,200	
Transmission			8-speed Sports Automatic Transmission			
WLTC mode fuel efficiency*		el efficiency*	12.2	12.7	13.1	
(km/liter)	No	ormal mode [*]	8.3	9.2	9.5	
	S	oort mode*	12.9	13.1	13.6	
	Hi	ghway mode [*]	14.7	14.7	15.1	
Suspensi	ion Fr	ont	MacPherson Strut			
	R	ear	Multi-link			
Brake	Fr	ont	Ventilated disc			
			4-pot aluminum monoblock caliper	Aluminum floating caliper		
	R	ear	Ventilated disc			
			Floating caliper	ting caliper Aluminum floating caliper		
Tire	Fr	ont	255/35ZR19	255/40R18	225/50R17	
	R	ear	275/35ZR19	275/40R18	255/45R17	

^{*}Evaluated value by the Ministry of Land, Infrastructure, Transport and Tourism

WLTC mode : Global driving mode composed of average driving hours in Normal, Sport, and Highway modes

Normal mode : Relatively slow speed driving affected by traffic signals, traffic congestion, and other similar factors is

assumed

Sport mode : Driving not affected by traffic signals, traffic congestion, or other similar factors is assumed.

Highway mode : Highway driving and other similar driving factors are assumed.